

1. Product and company identification

Product identifier

Trade name: HoofLox Acetone-Free Aerosol Hoof & Shoe Cleaner, 600ml

This safety data sheet pertains to the following products:
HoofLox Hoof and Shoe Cleaner 670784022736

Relevant identified uses of the substance or mixture and uses advised against

General use: Cleaning agent

Details of the supplier of the safety data sheet

Company name: EasyCare Inc.

Street/POB-No.: 89 Trimble Crossing Dr Bldg E

Postal Code, city: CO 81301 Durango – Colorado
USA

WWW: www.easycareinc.com

E-mail: admin@easycareinc.com

Telephone: +1 800.447.8836

Telefax: +1 800.447.2223

Department responsible for information:

Sam Glaser

Telephone: +1 800.447.8836 x2223, E-mail: sglaser@easycareinc.com

Emergency phone number

Sam Glaser

Telephone: +1 800.447.8836 x2223

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid

Color: colorless

Odor: Petroleum

Classification: Flammable Liquid - Category 2. Skin Irritation - Category 2.
Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity -
Category 1. Aquatic toxicity - chronic - Category 2.

Hazard symbols:



Signal word:

Danger

Hazard statements:

Highly flammable liquid and vapor.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

**HoofLox Acetone-Free Aerosol Hoof
& Shoe Cleaner, 600ml**

Material number HL-HSC-600

Revision date: 6/2/2025
Version: 1.0
Replaces version: 0.0
Language: en-US
Date of print: 6/2/2025

Page: 2 of 11

Precautionary statements: Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing vapors.
Wash hands and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN: Wash with plenty of water/soap.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
Specific treatment (see ' First aid ' on this label).
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use ... to extinguish.
Collect spillage.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may have a narcotic effect.
Special danger of slipping by leaking/spilling product.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Mixture of the substances listed below with non-hazardous additions:

Relevant ingredients:

CAS No.	Designation	Concentration	Classification
CAS 64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	50 - 100 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 110-54-3	n-Hexane	< 2.5 %	Flammable Liquid - Category 2. Skin Irritation - Category 2. Reproductive toxicant - Category 2. Specific Target Organ Toxicity (Single Exposure) - Category 3. Specific Target Organ Toxicity (Repeated Exposure) - Category 2. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.

Additional information: Labeling for contents according to regulation (EC) No 648/2004, annex VII:
Contains: 30 % and more aliphatic hydrocarbons

4. First aid measures

General information:	IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection! If medical advice is needed, have product container or label at hand.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice. Immediately get medical attention.
Following skin contact:	Wash with generous amount of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
After swallowing:	Drink large quantities of water. Do not induce vomiting. Danger of aspiration! Never give anything by mouth to an unconscious person. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Most important symptoms/effects, acute and delayed

May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Causes skin irritation.
Inhaling can lead to irritations of the respiratory tract and mucous membrane. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).
unconsciousness, shortage of breath, headache, drowsiness, dizziness, Cough, Nausea.

Information to physician

Aspiration hazard: in case of swallowing or vomiting danger of penetration into the lungs.
Subsequent observance for pneumonia and lung oedema.

5. Fire fighting measures

Flash point/flash point range:	3.2 °F (EN ISO 13736)
Auto-ignition temperature:	> 446 °F (ASTM E 659)
Suitable extinguishing media:	Water spray jet, alcohol resistant foam, Extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
Full water jet.

Specific hazards arising from the chemical

Highly flammable liquid and vapor.

Air combined with vapors may form potentially explosive mixtures that are heavier than air. Vapors may proceed on the ground over great distances and cause fire and backflashes.

May form dangerous gases and vapors in case of fire. Furthermore, there may develop: aldehyde, carbon black, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. Do not breathe fumes.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion.

Cool endangered containers with water spray and, if possible, remove from danger zone. Keep containers cool with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions:

Avoid breathing vapors. Eliminate all ignition sources if safe to do so. If possible, eliminate leakage.

Provide adequate ventilation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

Avoid contact with the substance. Keep unprotected people away. Cordon off downwind area at risk and warn inhabitants.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out). Never return spills in original containers for re-use.

Use explosion-proof equipment and non-sparking tools/utensils.

Additional information:

Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Avoid breathing vapors. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Avoid contact with the substance.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.

Guarantee sufficient ventilation during and after use, in order to prevent vapor accumulation.

Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.

Storage

Requirements for storerooms and containers:

Store in a well-ventilated place. Keep container tightly closed.
Store in a dry place. Store in a closed container. Keep only in original container.
Protect from heat and direct sunlight. Store containers in upright position.

Hints on joint storage:

Do not store together with oxidizing agents or strong acids. Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
110-54-3	n-Hexane	USA: ACGIH: TWA	176 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		USA: IDLH: TWA	1,100 ppm [10% LEL]
		USA: NIOSH: TWA	180 mg/m ³ ; 50 ppm
		USA: OSHA: TWA	1,800 mg/m ³ ; 500 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
110-54-3	n-Hexane	USA: ACGIH-BEI, urine	0.5 mg/L	2,5-Hexanedion	end of exposure or end of shift

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material:
Nitrile rubber, Fluororubber (Viton) or PVA (Polyvinyl alcohol)
Layer thickness: > 0.55 mm
Breakthrough time: > 480 min
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

**HoofLox Acetone-Free Aerosol Hoof
& Shoe Cleaner, 600ml**

Material number HL-HSC-600

Revision date: 6/2/2025
Version: 1.0
Replaces version: 0.0
Language: en-US
Date of print: 6/2/2025

Page: 6 of 11

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
Use combination filter type A2-P2 according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing vapors. Do not get in eyes, on skin, or on clothing.
Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse.
When using do not eat or drink. Wash hands thoroughly after handling.
Work place should be equipped with a shower and an eye rinsing apparatus.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Appearance:	Physical state at 68 °F and 101.3 kPa: liquid Color: colorless
Odor:	Petroleum
Odor threshold:	No data available
pH:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	181.4 - 226.4 °F (EN ISO 3405)
Flash point/flash point range:	3.2 °F (EN ISO 13736)
Evaporation rate:	3 (DIN 53170)
Flammability:	Highly flammable liquid and vapor.
Explosion limits:	LEL (Lower Explosion Limit): 0.80 Vol-% UEL (Upper Explosive Limit): 8.00 Vol-%
Vapor pressure:	at 68 °F: ≤ 70 hPa
Vapor density:	Not determined
Density:	at 59 °F: 695 kg/m ³ (ISO 12185)
Solubility:	Not determined
Water solubility:	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	> 446 °F (ASTM E 659)
Thermal decomposition:	Not determined
Viscosity, dynamic:	Not determined
Viscosity, kinematic:	Not determined
Explosive properties:	Product is not explosive. Vapors may form explosive mixtures with air.
Oxidizing characteristics:	Not oxidising
Solvent content:	100 %

10. Stability and reactivity

Reactivity:	Highly flammable liquid and vapor. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	Heating will lead to pressure increase: Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect from direct sunlight.
Incompatible materials:	Oxidizing agents, strong acids
Hazardous decomposition products:	No decomposition when used properly.
Thermal decomposition:	Not determined

11. Toxicological information

Toxicological tests

Toxicological effects:	The statements are derived from the properties of the single components. No toxicological data is available for the product as such. Acute toxicity (oral): Based on available data, the classification criteria are not met. Acute toxicity (dermal): Based on available data, the classification criteria are not met. Acute toxicity (inhalative): Based on available data, the classification criteria are not met. Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation. Serious eye damage/irritation: Based on available data, the classification criteria are not met. Product can cause slight irritation. Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met. Skin sensitisation: Based on available data, the classification criteria are not met. Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness. Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met. Aspiration hazard: Aspiration Toxicity - Category 1 = May be fatal if swallowed and enters airways.
Other information:	Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics: LD50 Rat, oral: > 5,840 mg/kg LD50 Rat, dermal: > 2,920 mg/kg LC50 Rat, inhalative (vapor): > 23.3 mg/L/4h (OECD 403)

Symptoms

unconsciousness, shortage of breath, headache, drowsiness, dizziness, Cough, Nausea.
Higher doses may lead to a narcotic effect.

12. Ecological information

Ecotoxicity

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Algae toxicity:

ErL50 Pseudokirchneriella subcapitata (green algae): 10 - 30 mg/L/72h (OECD 201)

NOELR Pseudokirchneriella subcapitata (green algae): 6.3 mg/L/72h (OECD 201)

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 3 mg/L/48h (OECD 202)

NOELR Daphnia magna (Big water flea): 1 mg/L/21d (OECD 211)

Fish toxicity:

LL50 Oncorhynchus mykiss: > 13.4 mg/L/96h (OECD 203)

NOELR Oncorhynchus mykiss: 1.53 mg/L/28d (QSAR Petrotox)

Mobility in soil

No data available

Persistence and degradability

Further details:

Biodegradability:

Information about Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics: 98 %/ 28d (OECD 301F), readily biodegradable.

Additional ecological information

Volatile organic compounds (VOC):

100 % by weight / 695 g/L

General information:

Do not allow to enter into ground-water, surface water or drains.

Avoid spills and leaks. Very small amounts contaminates drinking water.

13. Disposal considerations

Product

Recommendation:

Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Do not dispose of with household waste. Do not allow to enter into ground-water, surface water or drains.

Package

Recommendation:

Dispose of waste according to applicable legislation.

Handle contaminated packages in the same way as the substance itself.

Handle empty containers with care. Incineration may cause explosion.

14. Transport information

UN number

ADR/RID, IMDG, IATA-DGR:

UN 3295

UN proper shipping name

ADR/RID, IATA-DGR:

UN 3295, HYDROCARBONS, LIQUID, N.O.S.

IMDG:

UN 3295,

HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics),
MARINE POLLUTANT

Transport hazard class(es)

ADR/RID: Class 3, Code: F1
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3

Packing group

ADR/RID, IMDG, IATA-DGR:
II

Environmental hazards

Marine pollutant: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

USA: Department of Transportation (DOT)

Identification number: UN3295
Proper shipping name: UN 3295, HYDROCARBONS, LIQUID, N.O.S.
Hazard class or Division: 3
Packing Group: II
Labels: 3
Special Provisions: 144, IB2, T7, TP1, TP8, TP28
Packaging – Exceptions: 150
Packaging – Non-bulk: 202
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 5 L
Quantity limitations – Cargo only: 60 L
Vessel stowage – Location: B

Sea transport (IMDG)

UN number: UN 3295
Proper shipping name: UN 3295,
HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C7, n-alkanes,
isoalkanes, cyclics), MARINE POLLUTANT
Class or division, Subsidiary risk: Class 3, Subrisk -
Packing Group: II
EmS: F-E, S-D
Special Provisions: -
Limited quantities: 1 L
Excepted quantities: E2
Package - Instructions: P001
Package - Provisions: -
IBC - Instructions: IBC02
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T7
Tank instructions - Provisions: TP1, TP8, TP28
Stowage and handling: Category B.
Properties and observations: Immiscible with water.
Marine pollutant: yes
Segregation group: none





SAFETY DATA SHEET

according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 6/2/2025
Version: 1.0
Replaces version: 0.0
Language: en-US
Date of print: 6/2/2025

HoofLox Acetone-Free Aerosol Hoof & Shoe Cleaner, 600ml

Material number HL-HSC-600

Page: 10 of 11

Air transport (IATA)

UN/ID number: UN 3295
Proper shipping name: UN 3295, HYDROCARBONS, LIQUID, N.O.S.
Class or division, Subsidiary risk: Class 3
Packing Group: II
Hazard label: Flamm. liquid
Excepted Quantity Code: E2
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y341 - Max. Net Qty/Pkg. 1 L
Passenger and Cargo Aircraft: Pack.Instr. 353 - Max. Net Qty/Pkg. 5 L
Cargo Aircraft only: Pack.Instr. 364 - Max. Net Qty/Pkg. 60 L
Special Provisions: A3 A324
Emergency Response Guide-Code (ERG): 3H

15. Regulatory information

National regulations - U.S. Federal Regulations

n-Hexane: TSCA Inventory: listed
Clean Air Act:
CAA Hazardous Air Pollutants: yes
CAA SOCM Chemical: yes
Other Environmental Laws:
CERCLA: RQ 5000 lbs.
SARA Title III - Section 313, Toxic Release: Conc. 1.0% / Threshold Standard
NIOSH Recommendations:
Occupational Health Guideline: 0322

National regulations - U.S. State Regulations

n-Hexane: California Proposition 65: cancer
California Proposition 65 code: -
Delaware Air Quality Management List:
DRQ: 5000 - RQ State: Federal Regulations Apply
Idaho Air Pollutant List:
Title 585: AAC: 9 - EL: 12 - OEL: 180 - Title 586: -
Maine Hazardous Air Pollutants:
Me 2005: HAP - Hap Rpt: 2000
Massachusetts Haz. Substance codes: 2,4,5,6
Minnesota Haz. Substance:
Codes: ANO - Ratings: 9.57 - Status: Air Pollutant Title III. TRI.
New Jersey RTK Hazardous Substance:
DOT: 1208 - Sub No.: 1340 - TPQ: -
New York List of Hazardous Substances:
RQ-Air: 1 - RQ-Land: 1 - Note: No Note Associated with this chemical.
Pennsylvania Haz. Substance code: -
Washington Air Contaminant:
TWA: 50 ppm - 180 mg

16. Other information

Text for labeling: Contains 50 - 100 % Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, < 2.5 %
n-Hexane.
Labeling for contents according to regulation (EC) No 648/2004, annex VII:
Contains: 30 % and more aliphatic hydrocarbons



SAFETY DATA SHEET

according to 29 CFR 1910.1200 and ANSI standard Z400.1-2010


HoofLox Acetone-Free Aerosol Hoof & Shoe Cleaner, 600ml

Material number HL-HSC-600

Revision date: 6/2/2025
Version: 1.0
Replaces version: 0.0
Language: en-US
Date of print: 6/2/2025

Page: 11 of 11

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 4 (Severe)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate)

Flammability: 4 (Severe)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aquatic toxicity - chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Aspiration Toxicity: Aspiration toxicity
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
Flammable Liquid: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Reproductive toxicant: Reproductive toxicity
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Irritation: Skin irritation
STOT RE: Specific target organ toxicity - repeated exposure
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Date of first version: 6/2/2025

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.